



Technical Data Sheet

Article:	1229												
Model:	Welding Gloves ARGON II												
Sizes:	8, 9, 10, 11, 12												
For details on product dimensions and weights see below (table).													
Colour:	natural												
Length:	35 cm (approx.)												
Material:	Goat/sheep nappa leather												
Mat. thickness:	0,7-0,8 mm (approx.)												
Packaging:	120 pair / carton												
Subpackaging:	12 pair, bundled												
Details of packaging are below mentioned (table)													
Care instructions:													
PPE-category:	Category II - includes mean risks not listed under Cat. I or III, according to Regulation (EU) 2016/425, Annex I (published in the Official Journal of the European Union)												
Standardize:													
<u>EN 420:2003+A1:2009 - Protective gloves - General requirements and test methods</u>													
<u>EN 388:2016+A1:2018 - Protective gloves against mechanical risks</u>													
	<table border="0"> <tr> <td>Abrasion resistance</td> <td>3</td> </tr> <tr> <td>Cut resistance (Coupe test)</td> <td>1</td> </tr> <tr> <td>Tear resistance</td> <td>2</td> </tr> <tr> <td>Puncture resistance</td> <td>1</td> </tr> <tr> <td>Cut resistance (TDM) according to EN ISO 13997:1999</td> <td>X</td> </tr> </table>	Abrasion resistance	3	Cut resistance (Coupe test)	1	Tear resistance	2	Puncture resistance	1	Cut resistance (TDM) according to EN ISO 13997:1999	X		
Abrasion resistance	3												
Cut resistance (Coupe test)	1												
Tear resistance	2												
Puncture resistance	1												
Cut resistance (TDM) according to EN ISO 13997:1999	X												
<u>EN 407:2004 - Protective gloves against thermal risks</u>													
	<table border="0"> <tr> <td>burning behavior</td> <td>4</td> </tr> <tr> <td>contact heat</td> <td>1</td> </tr> <tr> <td>convective heat</td> <td>2</td> </tr> <tr> <td>Radiant heat</td> <td>X</td> </tr> <tr> <td>Small splashes of molten metal</td> <td>4</td> </tr> <tr> <td>Large splashes of molten metal</td> <td>X</td> </tr> </table>	burning behavior	4	contact heat	1	convective heat	2	Radiant heat	X	Small splashes of molten metal	4	Large splashes of molten metal	X
burning behavior	4												
contact heat	1												
convective heat	2												
Radiant heat	X												
Small splashes of molten metal	4												
Large splashes of molten metal	X												
<u>EN 12477:2001+A1:2005 - Protective gloves for welders</u>													
Type B For article related performance levels see EN standard in the text below.													
<u>EN 13594:2015 - Impact protection</u>													
Test result: X													
(X = not tested)													



© BIG Arbeitsschutz GmbH

Fittings:

Goat/sheep nappa leather, 5-finger design, unlined, pulse point protection thanks to the extra long cuff, wing thumb, material thickness: approx. 0,7-0,8 mm, glove length: approx. 35 cm (size 10)

Characteristics:

Comfortable to wear, heat-resistant, robust and resilient, with excellent pulse point protection thanks to the extra long cuff. With a 5-finger design for more freedom of movement and improved grip.

Application:

Applicable for welding and deburring work, other coarse work with medium risks (regarding mechanical risks), e.g. in the craft trade, construction sector, automotive industry, printing industry, metal industry, mechanical engineering industry, agricultural sector



Additional information regarding purpose, applications and risk assessment:

These products satisfy the requirements of the quoted standards. Please note that the actual conditions of use cannot be simulated and that the decision on the product's suitability for its intended purpose therefore lies exclusively with the user. The manufacturer is not responsible for improper use. Hence, an assessment of the residual risk should be performed before use in order to determine whether this product is suitable for its intended purpose. Kindly note the printed pictograms and performance levels.

Precautionary measures during use:

- These gloves must never be immersed in chemical substances or come into contact with chemical substances.
- Only use gloves with a printed chemical pictogram when handling chemicals.
- Make certain that the selected glove is resistant to the chemicals being used.
- Do not use these gloves to protect against serrated edges or blades, etc.
- If gloves must be used in a hot environment, make certain that they satisfy the requirements of EN 407:2004 and that they were tested as specified therein.
- Do not use the gloves close to moving machine parts.
- Check the gloves carefully before use to make certain there are no defects or imperfections.
- It is reasonable to assume that the gloves also protect against sharp objects such as injection needles, provided they satisfy the requirements of perforation resistance according to EN 388:2016+A1:2018.
- Discard damaged, worn, dirty or soiled gloves, irrespective of the substance (including on the inside), as they may lead to skin irritation and rashes. Consult a doctor or dermatologist should such cases arise.

EN 420:2003+A1:2009 - General requirements and test methods for gloves:

This standard specifies the relevant test methods to be used for all protective gloves and the general requirements for design principles, glove assembly, resistance of the glove material to water penetration, harmlessness, comfort and performance as well as the labeling to be carried out by the manufacturer and the information to be provided by the manufacturer.

EN 388:2016+A1:2018 - Protective gloves against mechanical risks:

Protective gloves against mechanical risks must achieve at least Level 1 or Level A in at least one of the properties (abrasion, cut, tear and puncture resistance) of the TDM cut resistance test according to EN ISO 13997:1999.

- Abrasion resistance: The number of cycles needed to wear through the test glove.
- Cut resistance: The number of test cycles in which the sample is cut through at constant speed.
- Tear resistance: The force needed to continue tearing the cut sample.
- Puncture resistance: The force needed to puncture the sample using a standardized test stylus.

EN 388:2016+A1:2018

Test criteria	Rating	Article 1229
A = Abrasion resistance	0 - 4	3
B = Cut resistance (Coupe test)	0 - 5	1
C = Tear resistance	0 - 4	2
D = Puncture resistance	0 - 4	1
E = Cut resistance (TDM) according to EN ISO 13997:1999	A - F	X
F = Impact protection test according to EN 13594:2015	P	X

The higher the test number, the better the test performance. X means 'not tested'. P means 'passed'.

Test	1	2	3	4	5
A = Abrasion resistance (number of abrasion cycles)	100	500	2000	8000	-
B = Cut resistance (index) Coupe test	1,2	2,5	5,0	10,0	20,0
C = Tear resistance (N)	10	25	50	75	-
D = Puncture resistance (N)	20	60	100	150	-

Test	A	B	C	D	E	F
E = Cut resistance according to EN ISO 13997:1999 (N)	2	5	10	15	22	30
Article 1229						

EN 13594:2015 - Impact protection:

Every area specified as providing protection against impact must be tested. The test method (dimensions of the test sample) does not permit impact testing of the finger protection. Gloves to protect against mechanical risks may be designed and manufactured in such a way that they offer specific impact damping (e.g. impact protection on the knuckles, the back of the hand, the palms). These gloves must satisfy the requirements of Level 1 according to EN 13594:2015.

The results of the Coupe test must only be taken as indications if blunting occurs during the cut resistance test (B), while the TDM cut resistance test (E) provides reference results in regard to performance.


WARNING:

The overall classification for gloves with two or more layers does not necessarily indicate the performance of the outermost layer. Gloves with mechanical resistance that achieve and demonstrate Level 1 tear resistance (C) or higher must not be worn if there is a risk of them catching when operating machines with moving parts. The tests refer to the palm of the gloves.

EN 407:2004 - Protective gloves against thermal risks


412X4X

test criteria	Possible ratings	Article 1229
A = burning behavior	0 - 4	4
B = contact heat	0 - 4	1
C = convective heat	0 - 4	2
D = Radiant heat	0 - 4	X
E = Small splashes of molten metal	0 - 4	4
F = Large quantities of molten metal	0 - 4	X

The letter 'X' in place of a number indicates that the glove is not intended for the purpose covered by this test.

Test	Test result according to EN407	1	2	3	4
Burning behaviour:	Burn time (s)	≤20	≤10	≤3	≤2
	Glow time (s)	-	≤120	≤25	≤5
Contact heat:	Contact temperature °C	100	250	350	500
	Threshold time (s)	≥15	≥15	≥15	≥15
Convective heat:	Heat transfer index HTI (s)	≥4	≥7	≥10	≥18
Radiant heat:	Heat transfer t24 (s)	≥7	≥20	≥50	≥95
Small splashes of molten metal:	Number of splashes	≥10	≥15	≥25	≥35
Large splashes of molten metal:	Molten iron (g)	30	60	120	200

WARNING:

Products with Level 1 or Level 2 rating for burning behaviour must not come into contact with a naked flame. The levels only apply to the entire product and all of its layers for gloves comprising several separable layers.

EN 12477:2001+A1:2005 - Protective gloves for welders:

These gloves are classified as Type A and Type B. Both types must be tested for the following criteria and must satisfy the minimum requirements defined for each type.

Requirement Anforderungen	Test according to CE standard	Minimum performance levels A	Minimum performance levels B	Article 1229 Type B
Abrasion resistance	EN 388	2	1	3
Blade cut resistance	EN 388	1	1	1
Tear resistance	EN 388	2	1	2
Puncture resistance	EN 388	2	1	1
Burning behaviour	EN 407	3	2	4
Contact heat resistance	EN 407	1	1	1
Convection heat resistance	EN 407	2	0	2
Resistance to small splashes of molten metal	EN 407	3	2	4
Dexterity	EN 420	1	4	5

After passing the test, the gloves must be marked with the number of the standard and the letter assigned to the type. The pictograms for thermal risks and mechanical risks must also be inserted.

Type B gloves are recommended if significant dexterity is required, e.g. for WIG welding. Type A gloves are recommended for all other types of welding.

WARNING:

There is currently no standardised method to test the UV transmission of glove materials. At present, however, protective gloves for welders are usually manufactured to prevent the transmission of UV radiation.

It is not possible to protect all live components of arc welding devices against direct contact. If gloves are to be worn for arc welding: These gloves do not protect against electric shock caused by defective devices or contact with live components. Gloves that are damp, dirty or full of perspiration have a reduced electric resistance, which compounds the risk of electric shock.

Markings on the gloves:

Trademark, art.-no. of manufacturer, size, CE-icon, at foodstuff suitability: glass and fork symbol, pictograms with the corresponding numbers of the relevant European PPE standards, i-mark, factory icon with date of manufacture: month/year

teXXor®



HANDSCHUHE >>

teXXor

1229

10



Brand label of manufacturer
Article no. of the manufacturer
Size of gloves (example)

Pictograms with the corresponding numbers of the relevant European PPE standards (example, detailed description in the text).



The CE marking confirms compliance with the requirements of European Regulation 2016/425.



i mark: Reference to the manufacturer's information.



Date of manufacture month/year: 00/0000

Dimensions/weights article:

Size	Length in cm	Width in cm	material thickness palm i	Weight in g/pair
8	35	12	0,8	135
9	35	13	0,8	145
10	35	14	0,8	145
11	35	14	0,8	148
12	35	15	0,8	166

The above values are approximate and subject to slight variations.

Details of packaging unit:

Size	kg gross	kg net	Length in cm	Width in cm	Height in cm
8	17,56	16,16	58	40	38
9	18,40	16,90	58	40	38
10	19,00	17,50	58	40	38
11	20,00	18,50	58	40	38
12	20,40	18,90	58	40	38

The above values are approximate and subject to slight variations.

Hazardous ingredients - REACH (Registration, Evaluation, Authorization and Restriction of Chemicals):

The product is manufactured in compliance with Annex XVII of the European REACH regulation 1907/2006 and contains no hazardous substances in concentrations requiring declaration.

Declaration of Conformity

CE These products are classified as personal protective equipment (PPE). The CE mark confirms that the product satisfies the applicable requirements of Regulation (EU) 2016/425.

Identification and selection:

Selection of model must be made according to workplace requirements, type of hazard and relevant environmental conditions. The employer is responsible for choosing the right PSA. Therefore, it is necessary to check the suitability of the product for the needs needed before use.

Regulation for use:

The product fulfil the safety requirements only if they are worn in an entirely correct manner and in their best condition. Check the product for defects or flaws before use. If any tears or holes appear during use of the product, they must be disposed of immediately. Make sure that the product are not too large or too small and fit exactly. Modifications to this PPE are not permitted. Follow the instructions provided in the manufacturer's information and keep this information in a safe place during the entire service life of the PPE. We assume no responsibility for any damages and/or consequences resulting from improper use.

Care instructions:





HANDSCHUHE >>

Do not wash and bleach the gloves. Drying in tumbler is not possible. Do not iron. Professional dry and wet cleaning is not allowed.

Both new and used gloves must be checked carefully for any damage before they are worn. Never store dirty gloves if they are intended for reuse. Users are advised to carefully remove the gloves on the right and then the left if it is not possible to remove the soiling or if doing so would present a danger. Here, use the hand wearing the glove in such a way that the other glove can be removed without coming into contact with the soiling.

Storage and aging:

The product should be stored in their original packaging in a dark, cool and dry place, away from direct sunlight and away from any sources of heat. Prolonged contact with direct sunlight or excessive heat will shorten the service life. Avoid any contact of the product with solvents which could result in changes to the product or its properties. The service life is generally up to 3 years when used and stored properly (see also expiry date on the packaging). The product are also marked with the production date (month/year).

Disposal:

Used products may be contaminated with environmentally harmful or hazardous substances. Dispose of in accordance with applicable local laws.

Health risks:

Allergies, caused by the proper use of the products, are not yet known. If an allergic reaction still occurs, consult a doctor or dermatologist.

First Aid:

Remove the product if they are contaminated with hazardous materials.
In case of contact with skin: immediately consult a doctor if an allergic reaction occurs.
In case of eye contact: wash out the affected eye with water. Consult a doctor immediately.

The notified body responsible for the EU Type Examination:

CTC
Parc Scientifique Tony Garnier
4 rue Hermann Frenkel
69367 Lyon Cedex 07
Frankreich
Kenn-Nr.: 0075

For the full Declaration of Conformity and manufacturer's information, please visit:
www.big-arbeitsschutz.de



issued on 05.02.2024/Rev.04